



Ду	NPS	Ступень давления	ØK	ØV	n	ØX	B	кг	Ду	NPS	Ступень давления	ØK	ØV	n	ØX	B	кг
50	2"	Py10 – Py40	157	125	4	M16	90°	5,4	150	6"	Py10 / Py16	294	240	8	M20	45°	15,3
		Class 150		120,7	4	5/8" UNC	90°				250		8	M24	45°		
		Class 300		127	8	5/8" UNC	45°				241,3		8	3/4" UNC	45°		
65	2 1/2"	Py10 / Py16	185	145	4	M16	90°	6,8	200	8"	Py10	335	295	8	M20	45°	22,0
		Py25 / Py40		145	8	M16	45°				298,5		8	3/4" UNC	45°		
		Class 150		139,7	4	5/8" UNC	90°				295		12	M20	30°		
		Class 300		149,3	8	3/4" UNC	45°						310	12	M24	30°	
80	3"	Py10 – Py40	204	160	8	M16	45°	7,7	200	8"	374	295	12	M20	30°	28,5	
		Class 150		152,4	4	5/8" UNC	90°					320	12	M27	30°		
		Class 300		168,1	8	3/4" UNC	45°					330,2	12	7/8" UNC	30°		
100	4"	Py10 / Py16	236	180	8	M16	45°	9,4	250	10"	435	350	12	M20	30°	40,0	
		Py25 / Py40		190	8	M20	45°					355	12	M24	30°		
		Class 150		190,5	8	5/8" UNC	45°					370	12	M27	30°		
		Class 300		200,2	8	3/4" UNC	45°					385	12	M30	30°		
				362	12	7/8" UNC	30°										
125	5"	Py10 / Py16	271	210	8	M16	45°	12,8	300	12"	474	400	12	M20	30°	52,0	
		Py25 / Py40		220	8	M24	45°					410	12	M24	30°		
		Class 150		215,9	8	3/4" UNC	45°					431,8	12	7/8" UNC	30°		
		Class 300		235	8	3/4" UNC	45°										

Макс. нагрузка: см. диаграмму соотношения температуры и давления

Остается право на изменения